

## CLAIMS

### WHAT IS CLAIMED:

1. A temperature sensor, comprising:

a device adapted to provide a first signal having a parameter responsive to temperature;

5 and

a generator adapted to provide a reference signal having a parameter that is substantially  
consistent over a preselected temperature range;

a comparator electrically coupled to the device and the generator and adapted to provide a  
second signal in response to the parameter of the first signal differing from the  
10 parameter of the reference signal; and

a digital filter coupled to the comparator and adapted to provide a third signal in response  
to receiving the second signal for a preselected duration of time.

2. A temperature sensor, as set forth in claim 1, wherein the comparator is further  
15 adapted to deliver the second signal in response to the parameter of the first  
signal rising above the parameter of the reference signal, and to discontinue  
delivery of the second signal in response to the parameter of the first signal  
falling below the parameter of the reference signal by a preselected magnitude.

3. A temperature sensor, as set forth in claim 1, wherein the comparator is further  
20 adapted to deliver the second signal in response to the parameter of the first  
signal falling below the parameter of the reference signal, and to discontinue  
delivery of the second signal in response to the parameter of the first signal  
rising above the parameter of the reference signal by a preselected magnitude.

4. A temperature sensor, as set forth in claim 1, wherein the comparator includes a hysteresis effect.

5. A temperature sensor, as set forth in claim 1, wherein the digital filter is adapted to provide the third signal in response to receiving a plurality of second signals over a preselected duration of time.

6. A temperature sensor, as set forth in claim 1, wherein the digital filter is adapted to provide the third signal in response to receiving a plurality of second signals over a preselected duration of time without interruption.

7. A temperature sensor, as set forth in claim 1, wherein the sensor is at least partially formed within a common substrate with the device.

8. A temperature sensor, as set forth in claim 1, wherein:  
the generator is adapted to provide a first and second reference signal, each having a parameter that is substantially consistent over a preselected temperature range;  
the comparator is electrically coupled to the device and the generator and adapted to provide a fourth signal in response to the parameter of the first signal being less than the parameter of the first reference signal, a fifth signal in response to the parameter of the first signal being greater than the first reference signal and less than the second reference signal, and a sixth signal in response to the parameter of the first signal being greater than the second reference signal; and  
the digital filter is coupled to the comparator and adapted to provide a seventh signal in response to receiving the fourth signal for a preselected duration of time, an eighth

signal in response to receiving the fifth signal for a preselected duration of time,  
and a ninth signal in response to receiving the sixth signal for a preselected  
duration of time.

5           9.     A temperature sensor, as set forth in claim 8, wherein the comparator  
             comprises first and second comparators.

          10.    A temperature sensor, as set forth in claim 8, wherein the comparator  
             comprises a multiplexer and a comparator, wherein the multiplexer is  
10           configured to selectively couple the first and second reference signals to the  
             comparator.

          11.    A temperature sensor, as set forth in claim 1, wherein:  
the generator is adapted to provide a first and second reference signal, each having a  
15           parameter that is substantially consistent over a preselected temperature range;  
the comparator is electrically coupled to the device and the generator and adapted to  
provide distinct signals in response to detecting the first signal being within  
distinct preselected ranges defined by the first and second reference signals.

20           12.    A method, comprising:  
generating a first signal having a parameter responsive to temperature; and  
generating a reference signal having a parameter that is substantially consistent over a  
preselected temperature range;  
generating a second signal in response to the parameter of the first signal differing from  
25           the parameter of the reference signal; and

generating a third signal in response to the second signal persisting for a preselected duration of time.

13. A method, as set forth in claim 12, wherein generating the second signal in response to the parameter of the first signal differing from the parameter of the reference signal further comprises delivering the second signal in response to the parameter of the first signal rising above the parameter of the reference signal, and discontinuing delivery of the second signal in response to the parameter of the first signal falling below the parameter of the reference signal by a preselected magnitude.

14. A method, as set forth in claim 12, wherein generating the second signal in response to the parameter of the first signal differing from the parameter of the reference signal further comprises delivering the second signal in response to the parameter of the first signal falling below the parameter of the reference signal, and discontinuing delivery of the second signal in response to the parameter of the first signal rising above the parameter of the reference signal by a preselected magnitude.

15. A method, as set forth in claim 12, wherein generating the second signal in response to the parameter of the first signal differing from the parameter of the reference signal further comprises includes generating the second signal with a hysteresis effect.

16. A method, as set forth in claim 12, wherein generating the third signal in response to the second signal persisting for a preselected duration of time further comprises providing the third signal in response to receiving a plurality of second signals over a preselected duration of time.

5

17. A method, as set forth in claim 12, wherein generating the third signal in response to the second signal persisting for a preselected duration of time further comprises providing the third signal in response to receiving a plurality of second signals over a preselected duration of time without interruption.

10

18. A method, as set forth in claim 12, wherein generating the first signal having a parameter responsive to temperature further comprises generating the first signal having a parameter responsive to a temperature associated with a semiconductor device.

15

19. A method, as set forth in claim 12, wherein:

generating the reference signal having a parameter that is substantially consistent over a preselected temperature range further comprises generating a first and second reference signal, each having a parameter that is substantially consistent over a preselected temperature range;

20

generating the second signal in response to the parameter of the first signal differing from the parameter of the reference signal further comprises providing a fourth signal in response to the parameter of the first signal being less than the parameter of the first reference signal, a fifth signal in response to the parameter of the first signal being greater than the first reference signal and less than the second reference

25

signal, and a sixth signal in response to the parameter of the first signal being greater than the second reference signal; and

generating the third signal in response to the second signal persisting for a preselected duration of time further comprises providing a seventh signal in response to receiving the fourth signal for a preselected duration of time, an eighth signal in response to receiving the fifth signal for a preselected duration of time, and a ninth signal in response to receiving the sixth signal for a preselected duration of time.

20. A temperature sensor, comprising:

means for generating a first signal having a parameter responsive to temperature; and  
means for generating a reference signal having a parameter that is substantially consistent over a preselected temperature range;  
means for generating a second signal in response to the parameter of the first signal differing from the parameter of the reference signal; and  
means for generating a third signal in response to the second signal persisting for a preselected duration of time.

21. A system, comprising:

a memory;

a microprocessor adapted to controllably access the memory; and

a temperature sensor, comprising:

a device adapted to provide a first signal having a parameter responsive to a temperature of said memory; and

a generator adapted to provide a reference signal having a parameter that is substantially consistent over a preselected temperature range;

a comparator electrically coupled to the device and the generator and adapted to provide a second signal in response to the parameter of the first signal differing from the parameter of the reference signal; and a digital filter coupled to the comparator and adapted to provide a third signal in response to receiving the second signal for a preselected duration of time.

5

10